


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | | |
|--|--|--|--|
| (51) International Patent Classification ⁶ : H04Q 3/00, 7/22 | | A1 | (11) International Publication Number: WO 99/60801 |
| | | | (43) International Publication Date: 25 November 1999 (25.11.99) |
| (21) International Application Number: PCT/SE99/00875 | | (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). | |
| (22) International Filing Date: 21 May 1999 (21.05.99) | | | |
| (30) Priority Data: 60/086,280 21 May 1998 (21.05.98) US 09/282,832 31 March 1999 (31.03.99) US | | | |
| (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). | | | |
| (72) Inventors: STILLE, Mats; Åsögatan 116, S-116 24 Stockholm (SE). NYBERG, Anna; Mjölnerstigen 13, S-181 46 Lidingö (SE). MARTLEW, Paul; Drottsvägen 16, S-191 33 Sollentuna (SE). | | | |
| (74) Agent: ERICSSON RADIO SYSTEMS AB; Common Patent Dept., S-164 80 Stockholm (SE). | | | |
| | | Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> | |

(54) Title: INTELLIGENT NETWORK AND PACKET DATA NETWORK INTEROPERABILITY



(57) Abstract

A method and system are disclosed for creating an interface (23) between a packet-switched network (16) and an IN, which is based on an interface between an associated circuit-switched network and an IN/CAMEL service (120). Meanwhile, the CAMEL application can also provide IN services to mobile subscribers (12) while they are roaming in other networks (e.g., international roaming).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | | | TR | Turkey |
| BG | Bulgaria | HU | Hungary | ML | Mali | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MN | Mongolia | UA | Ukraine |
| BR | Brazil | IL | Israel | MR | Mauritania | UG | Uganda |
| BY | Belarus | IS | Iceland | MW | Malawi | US | United States of America |
| CA | Canada | IT | Italy | MX | Mexico | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NE | Niger | VN | Viet Nam |
| CG | Congo | KE | Kenya | NL | Netherlands | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NO | Norway | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | NZ | New Zealand | | |
| CM | Cameroon | KR | Republic of Korea | PL | Poland | | |
| CN | China | KZ | Kazakhstan | PT | Portugal | | |
| CU | Cuba | LC | Saint Lucia | RO | Romania | | |
| CZ | Czech Republic | LI | Liechtenstein | RU | Russian Federation | | |
| DE | Germany | LK | Sri Lanka | SD | Sudan | | |
| DK | Denmark | LR | Liberia | SE | Sweden | | |
| EE | Estonia | | | SG | Singapore | | |

-1-

INTELLIGENT NETWORK AND PACKET DATA NETWORK INTEROPERABILITY

CROSS-REFERENCES TO RELATED APPLICATIONS

This Application for Patent claims the benefit of priority from, and hereby incorporates by reference the entire disclosure of, co-pending U.S. Provisional Application for Patent Serial No. 60/086,280, filed May 21, 1998.

BACKGROUND OF THE INVENTION

Technical Field of the Invention

The present invention relates in general to the telephony field and, in particular, to a method and system for attaining interoperability between an Intelligent Network (IN) and Packet Data Network (PDN).

Description of Related Art

Packet-switched communications standards have been specified for digital cellular telecommunications systems in both Europe and Japan. For example, standards for the General Packet Radio Service (GPRS) have been specified for the Pan-European Global System for Mobile Communications (GSM) by the European Telecommunications Standards Institute (ETSI), the Packet Personal Digital Cellular (PPDC) System by the Nippon Telephone and Telegraph Company (NTTC) in Japan, and packet-switched standards are being specified for the International Mobile Telecommunications-2000 (IMT-2000) System. These packet-switched communications systems being developed are considered more efficient than conventional circuit-switched communications systems in transferring information such as audio, video and data in a mobile radiotelephone system environment. Albeit, the efficiency is likely higher for circuit-switched voice, but the efficiency is higher for packets than the same coding used for circuit-switched data. However, it is assumed that in the initial operational years, the packet-switched communications systems will be used primarily for accessing and transferring Intranet (e.g., companies' local networks) and Internet (e.g., World-Wide Web or WWW) data, while the conventional circuit-switched systems will still provide the traditional bearer services (e.g., voice calls).

-2-

For some time now, mobile communications network operators (e.g., GSM, PDC and IMT-2000 network operators) have been providing certain value-added services such as, for example, the new IN/Customized Applications for Mobile network Enhanced Logic (CAMEL) service. CAMEL is a feature in the GSM Standard that integrates support of operator-specific IN services into the GSM architecture. Essentially, the CAMEL services are overlaid on top of the GSM circuit-switched traffic (e.g., voice calls). However, a problem that exists is that there is currently no known capability for overlaying these value-added services on packet-switched traffic. The main reason for this problem is that this capability is expected to be provided by the Intranet operator or Internet Service Provider (ISP), and not as part of the value-added service (e.g., IN/CAMEL) itself.

Currently, no international standard is being promulgated for an interface between an IN and packet-switched network, and as mentioned earlier, there is no known solution for the problem of how to provide value-added services (e.g., CAMEL) for packet-switched communications. As such, this is an immediate problem for mobile communications network operators who are currently providing IN services, such as, for example, the popular pre-paid services being offered for mobile subscribers' circuit-switched calls (e.g., voice calls and G3 facsimile calls). Such pre-paid IN services monitor the elapsed time of the circuit-switched call for a mobile subscriber, and translate that time into charges that are billed to the subscriber in proportion to the communications time used. However, there is currently no method or system available that enables a pre-paid IN service application to monitor the elapsed communications time for a subscriber using packet-switched communications.

Consequently, a pressing need has arisen for a PDN/IN interface and interoperability which will enable such services as IN/CAMEL to be overlaid on top of packet-switched traffic as a complement to conventional Intranet and Internet value-added services. As described in detail below, the present invention successfully meets this need and resolves these and other related problems.

SUMMARY OF THE INVENTION

In accordance with a preferred embodiment of the present invention, a method and system are provided for creating an interface between a packet-switched network and an IN, which is based on an interface between an associated circuit-switched network and an IN/CAMEL service. Meanwhile, the CAMEL application can also provide IN services to mobile subscribers while they are roaming in other networks (e.g., international roaming).

An important technical advantage of the present invention is that mobile network operators providing IN/CAMEL services to offer a pre-paid subscription to mobile users, which will cover traditional voice calls and also Intranet and Internet usage through a packet-switched communications standard.

Another important technical advantage of the present invention is that a mobile user of circuit-switched and packet-switched communications can subscribe with one network operator to provide a pre-paid service and pay in advance only once for the subscription. The network will subtract payments from the user's account for both the circuit-switched and packet-switched traffic.

Still another important technical advantage of the present invention is that a viable interface and interoperability are provided between a packet data node and an IN/CAMEL node, which can be used to overlay CAMEL services on packet communications as a service complement to Intranet and Internet value-added services.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be had by reference to the following detailed description when taken in conjunction with the accompanying drawings wherein:

FIGURE 1 is a block diagram of a system that can be used for connecting an IN/CAMEL service with a mobile packet data communications session, in accordance with a preferred embodiment of the present invention;

FIGURES 2A and 2B are related block diagrams that show additional parts of the system shown in FIGURE 1; and

-4-

FIGURE 3 is a block diagram of the system shown in FIGURES 1 and 2 in an exemplary scenario where the end-user is communicating via parallel connections, such as a circuit-switched connection and a packet-switched connection.

DETAILED DESCRIPTION OF THE DRAWINGS

The preferred embodiment of the present invention and its advantages are best understood by referring to FIGURES 1-3 of the drawings, like numerals being used for like and corresponding parts of the various drawings.

Essentially, in accordance with a preferred embodiment of the present invention, a method and system are provided for creating an interface between a packet-switched network and an IN which is based on an interface between an associated circuit-switched network and an IN/CAMEL service. Meanwhile, the CAMEL application can also provide IN services to mobile subscribers while they are roaming in other networks (e.g., international roaming).

Specifically, FIGURE 1 is a block diagram of a system 10 that can be used for connecting an IN/CAMEL service with a mobile packet data communications session, in accordance with a preferred embodiment of the present invention. As shown, a mobile phone 12 can register or initially attach (connect) to a packet network via a radio network control (RNC) 14. The receiving packet data communications node (e.g., referred to as a Serving GPRS Support Node or SGSN) 16 in the serving network interrogates the end-user's Home Location Register (HLR) 18 for certain subscription and security information that the HLR is expected to return. In response, the HLR 18 provides this information (e.g., authentication keys, etc.) to the SGSN 16. For this embodiment, this information from the HLR can also include a Service Key with the address of an IN/CAMEL service application in an IN Service Control Function (SCF) involved (described in more detail below), which enables the CAMEL service to enter the packet communications session. In accordance with the GSM Technical Specification for CAMEL Stage 2: GSM TS 03.78 (version 6.1.1 Release 1997), the Service Key can identify to the IN SCF the CAMEL service logic that should be applied. It is useful to note that in the future, an ISP may assume some or

-5-

all of the functions of an HLR. However, substituting an ISP for the HLR in the future should have no appreciable effect on the scope of the present invention. As such, the interface 22 between the SGSN 16 and the HLR 18 can be, for example, a Signalling System 7 (SS7) interface or an interface based on an Internet Protocol (IP). For example, the information can be conveyed over the SS7 interface in a message using a Mobile Application Part (MAP) protocol or an INAP protocol.

Referring to the block diagram shown in FIGURE 2A, the exemplary system 10 also includes the IN/CAMEL network's SCF 20, which can be used to implement the present invention. For example, in accordance with the CAMEL specification, a GSM (IN/CAMEL) SCF is a functional entity that contains the CAMEL service logic used to implement an Operator-Specific Service (OSS). Also, in accordance with the CAMEL specification, the (IN/CAMEL) SCF can interface with an HLR (18), a GSM Service Switching Function (SSF), and a GSM Specialized Resource Function (SRF) using a MAP or CAMEL AP (CAP) protocol.

When a mobile phone (12) activates a packet data communications session (e.g., immediately or sometime after the registration or attachment phase), the SGSN 16 sends a CAMEL-related signal to the IN/CAMEL SCF 20. As such, the SGSN 16 had earlier determined the identity of the IN/CAMEL network during the initial registration or attachment phase described above. The CAMEL-related signal received at the SCF 20 notifies the IN/CAMEL network that a packet data session is about to be set up before the packet data connection phase is continued further. The main reason for this notification is to conserve connection capacity, for example, in the event that the subscriber's pre-paid service does not allow for additional packet data communications.

Referring to the block diagram shown in FIGURE 2A, the CAMEL-related signal sent from the SGSN 16 to the SCF 20 can be implemented as part of an existing message (e.g., "InitialDataProvide" or an Initial Detection Point (DP) message) in accordance with the CAMEL protocol, or as a new message. In accordance with the CAMEL specification (Paragraph 9.1.5.2), an Initial DP message contains certain information elements (IEs) including a Service Key. As described earlier, the Service Key can be used to address the correct CAMEL service application(s) within the SCF

(20).

In response, the IN/CAMEL SCF 20 can return information to the SGSN 16 in an "ApplyCharging" message. In accordance with the CAMEL specification (Paragraph 9.2.2), an ApplyCharging message is an Information Flow (IF) which is used for interacting from a GSM SCF with GSM SSF charging mechanisms in order to control the duration of a call. As such, the SCF 20 can use an ApplyCharging IF to instruct the SGSN 16 about how it is to function with respect to the end-user and/or SCF 20.

For this embodiment, the SCF 20 sends an ApplyCharging IF to the SGSN 16, which provides information regarding the number of packet data bytes that the end-user can transmit. For example, the SCF 20 can send an ApplyCharging IF to the SGSN 16 with an IE including the value "1024,000,000". This information can be interpreted by the SGSN 16 to mean that the SGSN is to clear the packet connection when 1024 Mbits have been transmitted to/from the end-user from/to the packet data network. For this embodiment, the interface 23 between the SGSN 16 and SCF 20 can be, for example, an SS7 (MAP or CAP) or IP-based interface.

Referring to the block diagram shown in FIGURE 2B, in the event that the end-user clears the packet data session (by implicit or explicit deactivation) before the maximum bit limit is exceeded (e.g., 1024 Mbits), the SGSN 16 can send an IN/CAMEL message (e.g., "ApplyChargingReport" IF) to the SCF 20 in conjunction with the packet communications session clearing procedure. In accordance with the CAMEL specification (Paragraph 9.1.2), an ApplyChargingReport IF can be used by a GSM SSF to report to a GSM SCF information that was requested in an ApplyCharging IF. For this embodiment, an ApplyChargingReport IF can be used by the SGSN 16 to let the SCF 20 know how many bits were transmitted during the packet communications session. For example, an IE in the ApplyChargingReport IF can include the value "7,000,000" to represent the number of bits that were transmitted to/from the end-user during a previous packet data session. The SCF 20 can then subtract the previous session's "used" number of bits from the maximum number of bits available for use, in order to determine a new value representing the maximum number of bits that can be used for the next packet session (e.g., 7,000,000 bits subtracted from

-7-

the previous maximum of $1024,000,000 = 324,000,000$ bits). Alternatively, such an ApplyChargingReport IF can be used by the SGSN 16 to let the SCF 20 know a new maximum number of bits available for transmission.

FIGURE 3 is a block diagram of the system 10 in an exemplary scenario where the end-user is communicating via parallel connections, such as, for example, a circuit-switched connection (e.g., voice call) and a packet-switched connection (e.g., simultaneous use of e-mail). In this case, the IN/CAMEL part of the network should instruct the SGSN 16 to report back to the IN/CAMEL part of the network when a specified number of bits have been passed via both connections (e.g., 100,000,000 bits). This instruction is given so that the IN/CAMEL part of the network can, for example, provide the circuit-switched connection with less voice time during a period when more bits are being transmitted over the packet-switched connection. Consequently, this means that the upper limit of bits allowed for use in the packet session will decrease as the circuit-switched session is connected for a longer period of time. As such, during the packet data session, the IN/CAMEL part of the network has to be able to let the SGSN 16 know what the new value representing the maximum number of bits that can be allowed for transmission. For example, if 50,000 bits have been passed over the two connections since the last 100,000,000 bit report, preferably the SGSN 16 subtracts that 50,000 bits from a new upper limit received. Additionally, if needed, the SCF 20 can order (e.g., in an ApplyCharging IF) the SGSN 16 to report (e.g., in an ApplyChargingReport IF) every time that, for example, 100,000 bits have been passed. In sum, as described above, the present invention advantageously provides a viable interface and interoperability between a packet data node (e.g., SGSN) and an IN/CAMEL node (e.g., SCF), which can be used to overlay CAMEL services on packet communications, as a service complement to Intranet and Internet value-added services.

Although a preferred embodiment of the method and apparatus of the present invention has been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiment disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the invention as set forth and

defined by the following claims.

WHAT IS CLAIMED IS:

1. A method for establishing an interface between an intelligent network and a packet data network, comprising the steps of:
registering in said packet data network;
a receiving node in said packet data network requesting registration information from a database associated with said packet data network; and
said database returning to said receiving node said registration information and service information associated with said intelligent network.
2. The method of Claim 1, wherein said registering step is initiated by a mobile phone.
3. The method of Claim 1, wherein said database comprises a home location register.
4. The method of Claim 1, wherein said receiving node comprises a serving GPRS support node.
5. The method of Claim 1, wherein said service information comprises an IN/CAMEL service key.
6. The method of Claim 1, wherein said service information includes an address of a CAMEL application in a service control function of said intelligent network.
7. A method for establishing an interface between an intelligent network and a packet data network, comprising the steps of:
activating a communications session in said packet data network;
a node in said packet data network sending a notification signal to a node in said intelligent network, said notification signal identifying said communications session to said intelligent network; and

-10-

said node in said intelligent network sending a control signal to said node in said packet data network, said control signal including information to limit a duration of said communications session in said packet data network.

8. The method of Claim 7, wherein said node in said packet data network comprises a serving packet node.

9. The method of Claim 7, wherein said node in said intelligent network comprises a service control function.

10. The method of Claim 7, wherein said notification signal comprises sending initial data to a service.

11. The method of Claim 10, wherein said initial data includes a service key.

12. The method of Claim 7, wherein said control signal comprises a request from a service to apply pre-paid charging limits to a call.

13. The method of Claim 7, wherein said control signal includes a maximum value of packet data for transmission.

14. The method of Claim 13, further comprising the steps of:
if said duration of said communications session is limited to a value less than said maximum value of packet data for transmission, said node in said packet data network sending a second signal to said node in said intelligent network, said second signal including information associated with said duration; and

said node in said intelligent network using said duration information to determine a new maximum value of packet data for transmission.

15. The method of Claim 7, wherein said packet data network sends bit interval information to said intelligent network when a specified amount of data has

-11-

been transmitted, said bit interval information used by said intelligent network to determine a new maximum value of packet data for transmission.

16. A system for establishing an interface between an intelligent network and a packet data network, comprising:

means for registering a mobile phone in said packet data network;

a receiving node in said packet data network, said receiving node including means for requesting registration information from said packet data network; and

a database in said packet data network, said database including means for sending to said receiving node said registration information and service information associated with said intelligent network.

17. The system of Claim 16, wherein said database comprises a home location register.

18. The system of Claim 16, wherein said receiving node comprises a serving packet node.

19. The system of Claim 16 wherein said service information comprises an IN/CAMEL service key.

20. The system of Claim 16, wherein said service information includes an address of a CAMEL application in a service control function of said intelligent network.

21. A system for establishing an interface between an intelligent network and a packet data network, comprising:

means for activating a communications session in said packet data network;

a node in said intelligent network; and

a node in said packet data network, said node in said packet data network including means for sending a notification signal to said node in said intelligent

-12-

network, said notification signal identifying said communications session to said intelligent network, and said node in said intelligent network including means for sending a control signal to said node in said packet data network, said control signal including information to limit a duration of said communications session in said packet data network.

22. The system of Claim 21, wherein said node in said packet data network comprises a serving packet node.

23. The system of Claim 21, wherein said node in said intelligent network comprises a service control function.

24. The system of Claim 21, wherein said notification signal comprises sending initial data to a service.

25. The system of Claim 24, wherein said initial data includes a service key.





26. The system of Claim 21, wherein said control signal comprises a request from a service to apply pre-paid charging limits to a call.

27. The system of Claim 21, wherein said control signal includes a maximum value of packet data for transmission.

28. The system of Claim 27, further comprising:
said node in said packet data network including means for sending a session clear signal to said node in said intelligent network if said duration of said communications session is limited to a value less than said maximum value of packet data for transmission, said session clear signal including information associated with said duration, and means for using said duration information to determine a new maximum value of packet data for transmission.

-13-

29. The system of Claim 21, wherein said packet data network includes means for sending bit interval information to said intelligent network when a specified amount of data has been transmitted, and said intelligent network includes means for determining a new maximum value of packet data for transmission using said bit interval information.



INTERNATIONAL SEARCH REPORT

Inter. Appl. No.
PCT/SE 99/00875

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04Q3/00 H04Q7/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|------------------------------------|
| X | WO 95 26114 A (TELEFONAKTIEBOLAGET LM ERICSSON) 28 September 1995 (1995-09-28) abstract page 3, line 3 -page 4, line 7 page 6, line 12 -page 7, line 13 | 1-3, 7-10, 16-18, 21-24 |
| Y A | page 11, line 30 -page 12, line 26 page 14, line 13 - line 21 | 4, 5, 19 6, 11-15, 20, 26-29 |
| Y | WO 97 26739 A (NOKIA TELECOMMUNICATIONS OY) 24 July 1997 (1997-07-24) abstract page 1, line 25 -page 3, line 2 -/- | 4 |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

20 September 1999

Date of mailing of the international search report

04/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Larcinese, C

INTERNATIONAL SEARCH REPORT

Inter: onal Application No
PCT/SE 99/00875

| C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT | | |
|--|---|-----------------------|
| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| Y | <p>SMITH D G: "AN INTRODUCTION TO GSM ENHANCEMENTS FOR OPERATOR SPECIFIC SERVICES (CAMEL)" IEE COLLOQUIUM ON MOBILE COMMUNICATIONS TOWARDS THE NEXT MILLENIUM AND BEYOND, 17 May 1996 (1996-05-17), pages 6/1-6/09, XP000605991 page 1, line 21 - line 29 page 2, line 1 - line 7 -----</p> | 5,19 |

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SE 99/00875

| Patent document cited in search report | | Publication date | Patent family member(s) | Publication date |
|---|---|---------------------|----------------------------|---------------------|
| WO 9526114 | A | 28-09-1995 | AU 691601 B | 21-05-1998 |
| | | | AU 2153295 A | 09-10-1995 |
| | | | CA 2163428 A | 28-09-1995 |
| | | | EP 0702883 A | 27-03-1996 |
| | | | JP 9501813 T | 18-02-1997 |
| | | | SE 9400967 A | 23-09-1995 |
| WO 9726739 | A | 24-07-1997 | FI 960185 A | 16-07-1997 |
| | | | AU 1445897 A | 11-08-1997 |
| | | | EP 0875108 A | 04-11-1998 |

This Page Blank (uspto)